

Cased "A" Coils

TOSOT

TCAT**F(H)NAA

Project Name:

Location:

Engineer Name:

Purchaser:

Unit Designation:

Schedule No.

Submitted To:

Date:

General Features

- Built-In TXV with check valve
- Ideal for Dual Fuel applications
- Universal mounting orientation
- Precharged with 9oz. R410A
- Flared service valve connections



Coil Model

Outdoor Unit Model

TOSOT APEX

			TCAT24F/NaA	TCAT36F/NaA	TCAT48H/NaA	TCAT60H/NaA
			TUD36-24AH2ADU	TUD36-24AH2ADU	TUD60-24AH2ADU	TUD60-24AH2ADU
Rated Furnace Airflow		CFM	800	1000	1230	1510
Rated Blower Power		W	145	185	280	390
Capacity		Btu/h	24000	36000	48000	54000
EER	Cooling	Btu/(h·W)	12.5	12.2	11.7	11.7
SEER	Cooling	Btu/(h·W)	19.5	18	18	17
Pipe Size	Liquid	inch	3/8	3/8	3/8	3/8
	Gas	inch	3/4	3/4	3/4	3/4
Net Weight		lbs	64	64	95	95
Gross Weight		lbs	75	75	110	110
Loading Qty	40' GP	set	219	219	102	102
	40' HP	set	292	292	153	153

Note: The above performance data is tested at the "Rated Conditions" shown in the table

Model	Dimensions				
	W	D	H	Supply W	Supply D
TCAT(24)36F/NaA	17-1/2(445)	21-1/4(540)	23(584)	15-7/8(403)	19-3/8(492)
TCAT(48)60H/NaA	24-1/2(622)	21-1/4(540)	28-1/2(724)	22-7/8(581)	19-3/8(492)

For continual product development, the manufacturer reserves the right to change specifications without notice.



Americo HVAC Supply LLC



Tel: +1 877-298-7191

Email: info@tosotclima.com

Website: tosotclima.com

1266 San Luis Obispo Ave.
Hayward, CA. 94544