

Submittal Data: TM12H	KDI	12,000 BTU	J		
Job Name		Location Date			
Purchaser		Engineer			
Submitted To		For	Reference	Approval	Construction
Unit Designation		Schedule I	No.		
GENERAL FEATURES			-		
-Quiet Operation -Multi-Speed Fan					
-4-way Discharge Air					
-Internal Condensate Drain Pump				/	
-Swing Louver				- ×	
-Both Wireless & Wired Remote Controller	s		14.	_	
-Power Failure Recovery					
-Sentry Condensate Overflow Protection					
-Decorative Grille (Sold Separately)					
-Limited 5 yr. Parts Warranty					
System Ratir		Units Spe	cification & Da	ata	
Cooling*					
Rated Capacity	12,000 BTU/H				
		Wired Control	ler		XK-19
Heating*					
Rated Capacity	13,000 BTU/H	Air Filter			Netted polypropylene
Sound Pressure (Hi/Lo)**		Condensate D	Drain Lift (Height)	1	12-in
Cooling	46/32 dbA				305-mm
Heating	46/32 dbA	Drain Size (O	D)		1.2-in
					31-mm
Air Flow (min/max)					
Indoor Fan	265/353 CFM				
Electrical Rat		Refriger	ant Piping Dat	a	
Fan Motor		Refrigerant	Type		R410A
Output Power	11 W	ingorant	. 76 .		1110/1
FLA	0.2 A	Gas Pipe Si	ze (OD)		3/8-in
	0.2 M		20 (00)		5,0-11
Power Supply		Liquid Pipe	Size (OD)		1/4-in
Normal Operational Voltage	208/230 V, 1 Phase, 60 Hz		0.20 (0.2)		17 - 11
Voltage Range	187 - 253 V	Connection	Method		Flared
MCA	1.0 A	Connoction			, larea
Interconnecting Cable Wire Size	14-4 AWG				
		* Test condition	is are based on AH	RI 210/240	
			ratings are per AH		50
		.aango aro por Arr			
RATION	AHRI	CERTIFIED THE WWW.ahridirectory.org			ED
non azone-depleting refrigerant	200				LISTED

