

Submittal Data: TM24HI	KDI	24,000 BT	U		
Job Name		Location Date			
Purchaser		Engineer			
Submitted To		For	Reference	Approva	Construction
Unit Designation		Schedule	No.		
GENERAL FEATURES					
-Quiet Operation -Multi-Speed Fan					
-4-way Discharge Air					
-Internal Condensate Drain Pump					
-Swing Louver					1
-Both Wireless & Wired Remote Controllers	6		14		
-Power Failure Recovery					
-Sentry Condensate Overflow Protection					
-Decorative Grille (Sold Separately)					
-Limited 5 yr. Parts Warranty					
System Ratin		Units Spe	ecification &	Data	
Cooling*					
Rated Capacity	22,800 BTU/H				
		Wired Contro	oller		XK-19
Heating*					
Rated Capacity	27,400 BTU/H	Air Filter			Netted polypropylene
Sound Pressure (Hi/Lo)**		Condensate	Drain Lift (Height)	12-in
Cooling	49/45 dbA				305-mm
Heating	49/45 dbA	Drain Size (C))		1.2-in
					31-mm
Air Flow (min/max)					
Indoor Fan	500/694 CFM				
Electrical Rati	Refrigerant Piping Data				
	5		Nember		
Fan Motor		Refrigerant	t Type		R410A
Output Power	50 W	Ŭ			
FLA	0.4 A	Gas Pipe S	Size (OD)		5/8-in
Power Supply		Liquid Pipe	e Size (OD)		3/8-in
Normal Operational Voltage	208/230 V, 1 Phase, 60 Hz				
Voltage Range	187 - 253 V	Connection	n Method		Flared
MCA	1.0 A				
Interconnecting Cable Wire Size	14-4 AWG				
		* Test conditio	ns are based on AF	IRI 210/240.	
			er ratings are per AH		350
PATION					
	AHRI <u>o</u>	w.ahridirectory.org			KIN

24,000 BTUH MODEL

Model # C 24,000 BTUH 230V

Units: inch (mm)

