



TOSOT

SUBMITTAL DATA

Single Zone 18 Seer 18KBTU 230V

Model: TWH18ZR32DI / TWH18ZR32DO

Job Name

Location

Date

Purchaser

Engineer

Submitted to

For

Unit Designation

Schedule No.



YAP1F7F



TWH18ZR32DI



TWH18ZR32DO



XE71 (Optional)

GENERAL FEATURES:

- R32 Refrigerant
- High Efficiency DC Inverter Technology
- Compact and Quiet Design
- Wireless Remote with LCD Display
- Wired Controller Options
- Wi-Fi Included
- Low Ambient Cooling down to 0°F (Range 0°F to 115°F)
- Low Ambient Heating down to -13°F (Range -13°F to 75°F)
- Coil (Indoor and Outdoor) Copper Tube / Aluminum Fin

Americo HVAC Supply LLC



Tel: +1 877-298-7191
Email: info@tosotclima.com
Website: tosotclima.com

1266 San Luis Obispo Ave.
Hayward, CA. 94544



SPECIFICATIONS & FUNCTIONS:

Model		TWH18ZR32D
Power Supply	VAC / Phase / Hertz	208-230/1/60
Power Supply Mode	-	Outdoor
Cooling Capacity	Btu/h	18000
Heating Capacity	Btu/h	18000
Cooling Power Input	W	1758
Heating Power Input	W	1465
Rated Input	W	2200
Rated Current	A	10
EER	(Btu/h)/W	10.2
COP	(Btu/h)/W	12.28
SEER	SEER2	18
HSPF	HSPF2	8.2
Air Flow Volume(H-L)	CFM	589/506/471/435/400/335/282
Dehumidifying Volume	Pint/h	3.80
Application Area	sq ft	247-365
Controller Model	Remote	YAY1FF


Indoor Unit Model		TWH18ZR32DI
Fan Type	-	Cross-flow
Fan Diameter Length (D×L)	mm	108x691
Cooling Speed	r/min	1350/1200/1120/1050/980/860/750
Heating Speed	r/min	1350/1200/1120/1050/950/850/750
Fan Motor Power Output	W	45
Fan Motor RLA	A	0.7
Motor ratings	hp	0.067
Evaporator Form	-	Aluminum Fin-copper Tube
Evaporator Pipe Diameter	mm	φ5
Evaporator Row-fin Gap	mm	2-1.2
Evaporator Coil Length (L×D×W)	mm	700×22.8×381
Swing Motor Model	-	MP35CJ
Swing Motor Power Output	W	2.5
Fuse Current	A	3.15
Set Temperature Range	°F	61 ~ 86
Sound Pressure Level Cooling mode	dB (A)	51/47/45/43/41/37/33
Sound Power Level Cooling mode	dB (A)	61/57/55/53/51/47/43
Sound Pressure Level Heating mode	dB (A)	51/47/45/43/40/37/32
Sound Power Level Heating mode	dB (A)	61/57/55/53/50/47/42
Dimension (W x H x D)	inch	39 24/64 × 13 7/64 × 9 51/64
Net Weight	lb	35.3
Gross Weight	lb	41.8

Outdoor Unit Model		TWH18ZR32DO
Compressor Manufacturer	-	LANDA
Compressor Model	-	QXF-A120zF170A
Compressor Oil	-	FW68DA or equivalent
Compressor Type	-	Rotary
Compressor RLA	A	8.1
Compressor Power Input	W	1075
Outdoor Unit Fan Type	-	Axial-flow
Outdoor Unit Fan Diameter	mm	420
Fan Motor Speed	rpm	940
Fan Motor Power Output	W	30
Motor ratings	hp	0.04
Fan Motor RLA	A	1.2
Air Flow Volume	CFM	1483
Condenser Form	-	Aluminum Fin-copper Tube
Condenser Pipe Diameter	mm	φ7.94
Condenser Rows-fin Gap	mm	1-1.2
Condenser Coil Length (L×D×W)	mm	761.5×19.05×528
Permissible Excessive Operating Pressure for the Discharge Side	P.S.I.G.	624
Permissible Excessive Operating Pressure for the Suction Side	P.S.I.G.	363
Maximum Allowable Pressure	P.S.I.G.	624
Cooling Operation Ambient Temperature Range	°F	0 ~ 118
Heating Operation Ambient Temperature Range	°F	-13~75
Metering Device	-	Capillary
Defrosting Method	-	Automatic Defrosting
Sound Pressure Level (H)	dB (A)	58
Sound Power Level (H)	dB (A)	68
Dimension (WxHxD)	inch	31 37/64 × 21 27/32 × 13 25/32
Outdoor Unit Net Weight	lb	62.88
Outdoor Unit Gross Weight	lb	68.4
Refrigerant	--	R32
Factory Refrigerant Charge	oz	29.3
Connection Pipe Length	ft	24.6
Connection Pipe Gas Additional Charge	oz/ft.	0.2
Outer Diameter of Liquid Pipe	inch	1/4"
Outer Diameter of Gas Pipe	inch	1/2"
Max Distance Height	ft	32.8
Max Distance Length	ft	82.0

Functions				
Auto	Turbo	Quiet	Force Defrosting	Auto Fan
Cooling	Temperature	I Feel	Energy Saving	Intelligent Defrosting
Heating	Soft Start	Intelligent Preheating	8°C Heating Mode	Chassis Electric Heater Function
Dehumidify	Self-Diagnosis	Dry Anti-mildew Design	Turbo Cooling	Multi Speeds
Air Flow	Lock	Several Optional Filters	Low Ambient Cooling	Clock
Three Kinds of Sleep Mode	WIFI	Auto Clean	Low Ambient Heating	Standby
Vertical Auto Swing	LCD (Back Light)	Timer Feature	Low Voltage Startup	Memory
Horizontal Auto Swing	LED			






Outline Dimension Diagram



Unit: inch

Model	W	H	D
ATC	32 7/8	10 53/64	7 7/8
	W1	W2	W3
	7 3/64	18 5/32	7 11/16



Unit:inch



TOSOT

Installation Dimension Diagram

